

# ANDROID POS



## ZQ-1010

### HIGHLIGHTS


- ▶ 10.1" Capacitive touch panel
- ▶ Android system
- ▶ Built-in thermal printer
- ▶ Camera integrated
- ▶ Multi data ports
- ▶ WiFi supported / 3G or 4G optional



Customer Display



Multi Ports



Camera



Capacitive Touch Panel

### SPECIFICATIONS

CPU	Rockchip RK3066 Dual-core Cortex-A9 1.5GHZ Quad-Core GPU Mail-400	Thermal Printer	58mm Thermal Printer, Max 60 mm/sec, Diameter Max. Ø60 mm, USB GB2312, PC437, Katakana, PC850, PC860, PC863, PC865, WPC1253, Iran, WPC1256, PC737, WPC1250, WPC1252, PC866, PC852, PC858, , User define		
RAM	DDR3 1GB		Optional Peripherals	MSR	RS232 DC5V±5%, 65mA (max)
Storage	NAND Flash 4GB Mini SD 32GB(max) Extendable			RFID	RS232 DC5V±5%, 65mA (max)
WI-FI	Optional 802.11 b/g/n WI-FI module	External Port	IC Card	RS232 DC5V±5%, 65mA (max)	
OS	Android 4.2		3 x USB, 1 x TF, 1 x LAN, 1 x DC12V Input, 1 x Cash Drawer, 1 x RS232		
Language	English /Chinese /Russian /French /German /Italian /Spanish	Camera (Optional)	0.3MP 2D Barcode scanner		
Operator Display	10.1" diagonal, LED Back light, 1024×600, LVDS		Environment	Operating temperature and humidity: -10°C ~ 40°C, 20 ~ 80% RH	
Touch Screen	10.1" diagonal, Projected Capacitive touch, I2C	Storage temperature and humidity: -20°C ~ 50°C, 20 ~ 90% RH			
Customer Display (optional)	LED 9 Digit, DC5V, RS232, 9600BPS Characters: 0...9 LCD 2*20 Digit, DC5V, RS232, 9600BPS; ASCII code	Dimension		276(L) × 272 (W) × 95 (H) mm	
Power Supply	DC12V 5A				
Battery (optional)	8.4V 2200mAh				