

Contents

Vertical Multistage Centrifugal In-line Pumps



Pump



The SB, SBI and SBN pumps are non-self priming vertical multistage pump of in-line design, flange or with Victaulic coupling with equally sized suction and discharge ports. Stage construction with stainless steel impellers, chambers and pressure casing. Pump stub shaft and motor shaft of the IEC-standards motor are directly close coupled. All pumps are equipped with a cartridge type mechanical seal for easy maintenance.

SB, SBI and SBN pumps have different pump sizes and various numbers of stages to provide the flow and the pressure required.

Applications

WATER SUPPLY AND PRESSURE BOOSTING

Pressure boosting in buildings, hotels, residential complexes
Pressure booster stations, supply of water networks
Pressure boosting for industrial water supply

IRRIGATION AND AGRICULTURE

Greenhouses
Sprinkler irrigation
Field irrigation (flooding)

LIGHT INDUSTRY

Washing and cleaning systems
Car washing facilities
Fire fighting systems
Process water systems
Machine tools (cooling lubricants)

WATER TREATMENT

Water softeners and de-mineralization
Reverse Osmosis systems
Distillation systems
Filtration
Ultra-filtration systems


HEATING, VENTILATION AND AIR-CONDITIONING

Boilers
Induction heating
Heat exchangers
Refrigerators
Cooling towers and systems
Temperature control systems




Identification Code

SB - 10 - 5 - S Q Q E



Pump nameplate information



1. Pump Type - Seal Type
2. Pump Model
3. Frequency
4. Rated Power
5. Speed
6. Maximum Head
7. Capacity
8. Head Range
9. Maximum Operating Pressure
10. Rotating Direction
11. Serial number

Motor

- Squirrel cage in short circuit, aluminum casing up to 22 kW, totally enclosed, fan-cooled, 2-pole standard motor.
- Standard supply Stairs motors up to 1.1 kW. Other motor brands for higher powers.
- Electrical data
 - ⊙ Enclosure class: IP55
 - ⊙ Insulation class: F
 - ⊙ Standard voltages: P2: 0.37-7.5 KW: 3 x 220-240/380-415 V
 - P2: From 11 KW 3 x 380-415 V
- The motors have efficiency values that fall within the range normally referred to as high efficiency.
- Ambient temperature: Max. +50°C

Contents

Vertical Multistage Centrifugal In-line Pumps




STAIRS PUMPS

Motor Data

Motor Type				Nominal current in [A]				
HP	kW	Pole	Flange	Frame	3~220 V	3~240 V	3~380 V	3~415 V
0.5	0.37	2	B14	71A	1.8	1.9	1.0	1.1
0.75	0.55			71B	2.6	2.7	1.5	1.6
1.0	0.75			80A	3.4	3.6	2.0	2.1
1.5	1.1			80B	5.1	5.2	2.9	3.0
2.0	1.5			90S	6.0	6.2	3.5	3.6
3.0	2.2			90L	9.5	10.0	5.5	5.8
4.0	3.0			100L	12.1	12.5	7.0	7.2
5.5	4.0			112M	14.9	15.0	8.6	8.7
			B5		3~380V	3~415V	3~660V	3~690V
7.5	5.5			132S	12.1	12.0	7.0	6.9
10	7.5			132S	16.0	15.3	9.2	8.8
							3~380 V	3~415 V
15	11			160M			21.0	19.2
20	15			160M			28.4	26.0
25	18.5			160L			34.7	31.8
30	22			180M			41.1	37.7
40	30			200L			55.7	51.0
50	37			200L			68.3	62.5
60	45			225M			87.2	78.6
75	55			250M			101.0	92.5
100	75			280S			134.0	123.0

Mechanical Seal

Standard Cartridge type mechanical seal made of Silicon Carbide/Silicon Carbide/EPDM or Viton. Based on the type of application, alternative materials are available for the seal and the elastomers. The cartridge type mechanical seal can be replaced in minutes without special tools and without dismantling the pump.



List of Materials

Q : Silicon carbide	E : EPDM
U : Tungsten carbide	V : Viton
B : Carbon	

Type of Seal

Seal Type	SB/SBI/SBN		
	1/3/5/10/15/20 /32/45/64/90	120/150	
		0.5-60HP	75-100HP
Mechanical Seals			
S: O-ring seal Cartridge type	●	●	
B: Rubber bellows seal Cartridge type			●
QQ	●	●	●
UU	Optional	Optional	
QB	Optional	Optional	
UB	Optional	Optional	
Seals			
E	●	●	
V	●	●	●



Maximum operating and inlet pressures

50Hz

Stages	Maximum Operating Pressure	Stages	Maximum Inlet Pressures
SB, SBI, SBN 1			
2-36	25bar	2-36	10bar
SB, SBI, SBN 3			
2-36	25bar	2-29	10bar
		31-36	15bar
SB, SBI, SBN 5			
2-36	25bar	2-16	10bar
		18-36	15bar
SB, SBI, SBN 10			
1-16	16bar	1-6	8bar
17-22	25bar	7-22	10bar
SB, SBI, SBN 15			
1-10	16bar	1-3	8bar
12-17	25bar	4-17	10bar
SB, SBI, SBN 20			
1-10	16bar	1-3	8bar
12-17	25bar	4-17	10bar
SB, SBI, SBN 32			
(1-1)-7	16bar	(1-1)-4	4bar
(8-2)-14	30bar	(5-2)-10	10bar
		(11-2)-14	15bar
SB, SBI, SBN 45			
(1-1)-5	16bar	(1-1)-2	4bar
(6-2)-11	30bar	(3-2)-5	10bar
(12-2)-(13-2)	33bar	(6-2)-(13-2)	15bar
SB, SBI, SBN 64			
(1-1)-5	16bar	(1-1)-(2-2)	4bar
(6-2)-(8-1)	30bar	(2-1)-(4-2)	10bar
		(4-1)-(8-1)	15bar
SB, SBI, SBN 90			
(1-1) - 4	16bar	(1-1) - 1	4bar
(5-2) - 6	30bar	(2-1) - (3-2)	10bar
		3 - 6	15bar
SB, SBI, SBN 120			
1-7	30bar	1-(2-1)	10bar
		2-(5-1)	15bar
		(6-1)-7	20bar
SB, SBI, SBN 150			
(1-1)-6	30bar	(1-1)-1	10bar
		(2-1)-(4-2)	15bar
		(5-2)-6	20bar

* Rule to follow : The inlet pressure+ the pressure against a closed valve < Max. Operating pressure.



Contents

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Construction



CONSTRUCTION

Pos.	Name	Material	SB 1,3,5,10,15,20		SBI 1,3,5,10,15,20		SBN 1,3,5,10,15,20	
			Standard		Standard		Standard	
			Europe	USA	Europe	USA	Europe	USA
36	Pump head	Cast Iron	EN-GJL-200	ASTM 25B	EN-GJS-450-10	ASTM 65-45-12	EN-GJS-450-10	ASTM 65-45-12
56	Pump head cover	Stainless steel	N/A		1.4301	AISI 304	1.4401	AISI 316
18	Impeller	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
37	Shaft	Stainless steel	1.4057	AISI 431	1.4057	AISI 431	1.4401	AISI 316
48	Outer Sleeve	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
82	O-ring for outer sleeve	EPDM						
12	Chamber	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
24	Neck ring	PTFE						
59	Base	Cast Iron	EN-GJL-200	ASTM 25B	N/A			
	Base	Stainless steel	N/A		1.4301	AISI 304	1.4401	AISI 316
62	Base plate	Cast Iron	N/A		EN-GJL-200	ASTM 25B	EN-GJL-200	ASTM 25B
44	Coupling	Fe-Cu-C	SINT C11	MPIF FC0525	SINT C11	MPIF FC0525	SINT C11	MPIF FC0525
57	Mechanical seal	Cartridge type						


Contents

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Construction



CONSTRUCTION

Pos.	Name	Material	SB 32, 45, 64, 90		SBI 32, 45, 64, 90		SBN 32, 45, 64, 90	
			Standard		Standard		Standard	
			Europe	USA	Europe	USA	Europe	USA
36	Pump head	Cast Iron	EN-GJL-250	ASTM 35B				
		Stainless steel			1.4301	AISI 304	1.4401	AISI 316
53	Motor Bracket	Cast Iron	EN-GJL-250	ASTM 35B	EN-GJL-250	ASTM 35B	EN-GJL-250	ASTM 35B
18	Impeller	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
37	Shaft	Stainless steel	1.4057	AISI 431	1.4057	AISI 431	1.4401	AISI 316
48	Outer Sleeve	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
82	O-ring for outer sleeve	EPDM						
12	Chamber	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
24	Neck ring	Carbon Fiber + POB + PTFE						
59	Base	Cast Iron	EN-GJL-250	ASTM 35B	N/A			
	Base	Stainless steel		N/A	1.4301	AISI 304	1.4401	AISI 316
62	Base plate	Cast Iron		N/A	EN-GJL-250	ASTM 35B	EN-GJL-250	ASTM 35B
57	Mechanical seal	Cartridge type						
14	Bearing ring			Bronze			POB+ Graphite+ PTFE	
42	Bottom bearing ring	Tungsten carbide/ Tungsten carbide						



Contents

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Construction



CONSTRUCTION

Pos.	Name	Material	SB 120, 150		SBI 120, 150		SBN 120, 150	
			Standard		Standard		Standard	
			Europe	USA	Europe	USA	Europe	USA
36	Pump head	Cast Iron	EN-GJL-250	ASTM 35B	N/A			
		Stainless steel	N/A		1.4301	AISI 304	1.4401	AISI 316
53	Motor bracket (15HP~60HP)	Cast Iron	EN-GJL-250	ASTM 35B	EN-GJL-250	ASTM 35B	EN-GJL-250	ASTM 35B
	Motor bracket (75HP~100HP)	Cast Iron	EN-GJS-450-10	ASTM 65-45-12	EN-GJS-450-10	ASTM 65-45-12	EN-GJS-450-10	ASTM 65-45-12
17	bearing ring	PTFE						
18	Impeller	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
37	Shaft	Stainless steel	1.4057	AISI 431	1.4057	AISI 431	1.4401	AISI 316
48	Outer sleeve	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
82	O-ring for outer sleeve	EPDM						
12	Chamber	Stainless steel	1.4301	AISI 304	1.4301	AISI 304	1.4401	AISI 316
24	Neck ring	PTFE						
59	Base	Cast Iron	EN-GJL-250	ASTM 35B	N/A			
		Stainless steel	N/A		1.4301	AISI 304	1.4401	AISI 316
62	Base plate	Cast Iron	N/A		EN-GJS-450-10	ASTM 65-45-12	EN-GJS-450-10	ASTM 65-45-12
62A	Base plate	Cast Iron	EN-GJS-450-10	ASTM 65-45-12	EN-GJS-450-10	ASTM 65-45-12	EN-GJS-450-10	ASTM 65-45-12
57	Mechanical seal	Cartridge type						
42	Bottom bearing ring	SiC / SiC						




Contents

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 1




Contents

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SB 1



Pump type	Motor	SB				
		Dimension[mm]				Net weight [kg]
	P ₂	DIN flange		D1	D2	
	[kW]	H1	H2			
SB1-2	0.37	279	474	141	115	23.4
SB1-3	0.37	279	474	141	115	23.4
SB1-4	0.37	297	492	141	115	23.8
SB1-5	0.37	315	510	141	115	24.2
SB1-6	0.37	333	528	141	115	24.5
SB1-7	0.37	351	546	141	115	24.9
SB1-8	0.55	369	564	141	115	25.8
SB1-9	0.55	387	582	141	115	26.1
SB1-10	0.55	405	600	141	115	26.5
SB1-11	0.55	423	618	141	115	26.9
SB1-12	0.75	447	682	141	115	29.4
SB1-13	0.75	465	700	141	115	29.8
SB1-15	0.75	501	736	141	115	30.5
SB1-17	1.1	537	772	141	115	32.3
SB1-19	1.1	573	808	141	115	33.1
SB1-21	1.1	609	844	141	115	33.8
SB1-23	1.1	645	880	141	115	34.6
SB1-25	1.5	697	988	177	141	44.0
SB1-27	1.5	733	1024	177	141	44.8
SB1-30	1.5	787	1078	177	141	45.9
SB1-33	2.2	841	1132	177	141	49.9
SB1-36	2.2	895	1186	177	141	51.0


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SBI, SBN 1



Pump type	Motor	SBI , SBN							
		Dimension [mm]						Net weight [kg]	
		Victaulic		DIN flange		D1	D2	Victaulic	DIN flange
	P ₂ [kW]	H1	H2	H1	H2				
SBI,SBN1-2	0.37	257	452	282	477	141	115	19.3	20.2
SBI,SBN1-3	0.37	257	452	282	477	141	115	19.3	20.3
SBI,SBN1-4	0.37	275	470	300	495	141	115	19.7	20.6
SBI,SBN1-5	0.37	293	488	318	513	141	115	20.1	21.0
SBI,SBN1-6	0.37	311	506	336	531	141	115	20.4	21.4
SBI,SBN1-7	0.37	329	524	354	549	141	115	20.8	21.7
SBI,SBN1-8	0.55	347	542	372	567	141	115	21.7	22.6
SBI,SBN1-9	0.55	365	560	390	585	141	115	22.0	23.0
SBI,SBN1-10	0.55	383	578	408	603	141	115	22.4	23.3
SBI,SBN1-11	0.55	401	596	426	621	141	115	22.8	23.7
SBI,SBN1-12	0.75	425	660	450	685	141	115	25.2	26.1
SBI,SBN1-13	0.75	443	678	468	703	141	115	25.6	26.5
SBI,SBN1-15	0.75	479	714	504	739	141	115	26.3	27.2
SBI,SBN1-17	1.1	515	750	540	775	141	115	28.1	29.1
SBI,SBN1-19	1.1	551	786	576	811	141	115	28.8	29.8
SBI,SBN1-21	1.1	587	822	612	847	141	115	29.6	30.6
SBI,SBN1-23	1.1	623	858	648	883	141	115	30.4	31.3
SBI,SBN1-25	1.5	675	966	700	991	177	141	39.8	40.8
SBI,SBN1-27	1.5	711	1002	736	1027	177	141	40.6	41.5
SBI,SBN1-30	1.5	765	1056	790	1081	177	141	41.7	42.6
SBI,SBN1-33	2.2	819	1110	844	1135	177	141	45.6	46.6
SBI,SBN1-36	2.2	873	1164	898	1189	177	141	46.7	47.7


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 3




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SB 3



Pump type	Motor	SB				
		Dimension[mm]				Net weight [kg]
	P ₂	DIN flange		D1	D2	
	[kW]	H1	H2			
SB 3-2	0.37	279	474	141	115	23.4
SB 3-3	0.37	279	474	141	115	23.4
SB 3-4	0.37	297	492	141	115	23.8
SB 3-5	0.37	315	510	141	115	24.2
SB 3-6	0.55	333	528	141	115	25.0
SB 3-7	0.55	351	546	141	115	25.4
SB 3-8	0.75	375	610	141	115	27.9
SB 3-9	0.75	393	628	141	115	28.3
SB 3-10	0.75	411	646	141	115	28.7
SB 3-11	1.1	429	664	141	115	30.2
SB 3-12	1.1	447	682	141	115	30.5
SB 3-13	1.1	465	700	141	115	30.9
SB 3-15	1.1	501	736	141	141	31.6
SB 3-17	1.5	553	844	177	141	41.0
SB 3-19	1.5	589	880	177	141	41.8
SB 3-21	2.2	625	916	177	141	45.3
SB 3-23	2.2	661	952	177	141	46.1
SB 3-25	2.2	697	988	177	141	46.8
SB 3-27	2.2	733	1024	177	141	47.6
SB 3-29	2.2	769	1060	177	141	48.3
SB 3-31	3	809	1125	197	147	56.6
SB 3-33	3	845	1161	197	147	57.4
SB 3-36	3	899	1215	197	147	58.5


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SBI, SBN 3



Pump type	Motor	SBI , SBN							
		Dimension [mm]						Net weight [kg]	
		Victaulic		DIN flange		D1	D2	Victaulic	DIN flange
		H1	H2	H1	H2				
	P ₂ [kW]								
SBI,SBN3-2	0.37	257	452	282	477	141	115	19.3	20.2
SBI,SBN3-3	0.37	257	452	282	477	141	115	19.3	20.3
SBI,SBN3-4	0.37	275	470	300	495	141	115	19.7	20.6
SBI,SBN3-5	0.37	293	488	318	513	141	115	20.1	21.0
SBI,SBN3-6	0.55	311	506	336	531	141	115	20.9	21.9
SBI,SBN3-7	0.55	329	524	354	549	141	115	21.3	22.2
SBI,SBN3-8	0.75	353	588	378	613	141	115	23.7	24.6
SBI,SBN3-9	0.75	371	606	396	631	141	115	24.0	25.0
SBI,SBN3-10	0.75	389	624	414	649	141	115	24.4	25.4
SBI,SBN3-11	1.1	407	642	432	667	141	115	25.9	26.9
SBI,SBN3-12	1.1	425	660	450	685	141	115	26.3	27.2
SBI,SBN3-13	1.1	443	678	468	703	141	115	26.7	27.6
SBI,SBN3-15	1.1	479	714	504	739	141	115	27.4	28.3
SBI,SBN3-17	1.5	531	822	556	847	177	141	36.9	37.8
SBI,SBN3-19	1.5	567	858	592	883	177	141	37.6	38.5
SBI,SBN3-21	2.2	603	894	628	919	177	141	41.2	42.1
SBI,SBN3-23	2.2	639	930	664	955	177	141	41.9	42.9
SBI,SBN3-25	2.2	675	966	700	991	177	141	42.6	43.6
SBI,SBN3-27	2.2	711	1002	736	1027	177	141	43.4	44.3
SBI,SBN3-29	2.2	747	1038	772	1063	177	141	44.1	45.1
SBI,SBN3-31	3	787	1103	812	1128	197	147	52.0	53.0
SBI,SBN3-33	3	823	1139	848	1164	197	147	52.8	53.7
SBI,SBN3-36	3	877	1193	902	1218	197	147	53.9	54.8



Technical data

Vertical Multistage Centrifugal In-line Pumps




STAIRS PUMPS

SB, SBI, SBN 5





Dimensions and weights – SB 5



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
	[kW]	H1	H2				
SB 5-2	0.37	279	474	141	115	—	23.3
SB 5-3	0.55	306	501	141	115	—	24.2
SB 5-4	0.55	333	528	141	115	—	24.8
SB 5-5	0.75	366	601	141	115	—	27.4
SB 5-6	1.1	393	628	141	115	—	29.1
SB 5-7	1.1	420	655	141	115	—	29.6
SB 5-8	1.1	447	682	141	115	—	30.1
SB 5-9	1.5	490	781	177	141	—	39.3
SB 5-10	1.5	517	808	177	141	—	39.9
SB 5-11	2.2	544	835	177	141	—	43.2
SB 5-12	2.2	571	862	177	141	—	43.7
SB 5-13	2.2	598	889	177	141	—	44.2
SB 5-14	2.2	625	916	177	141	—	44.8
SB 5-15	2.2	652	943	177	141	—	45.2
SB 5-16	2.2	679	970	177	141	—	45.8
SB 5-18	3	737	1053	197	147	—	54.3
SB 5-20	3	791	1107	197	147	—	55.5
SB 5-22	4	845	1171	220	161	—	59.8
SB 5-24	4	899	1225	220	161	—	60.8
SB 5-26	4	953	1279	220	161	—	62.7
SB 5-29	4	1034	1360	220	161	—	64.6
SB 5-32	5.5	1145	1507	235	197	300	90.1
SB 5-36	5.5	1253	1615	235	197	300	92.6


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SBI, SBN 5



Pump type	Motor P ₂ [kW]	SBI, SBN								
		Dimension [mm]							Net weight [kg]	
		Victaulic		DIN flange		D1	D2	D3	Victaulic	DIN flange
		H1	H2	H1	H2					
SBI,SBN5-2	0.37	257	452	282	477	141	115	—	19.2	20.1
SBI,SBN5-3	0.55	284	479	309	504	141	115	—	20.3	21.2
SBI,SBN5-4	0.55	311	506	336	531	141	115	—	20.8	21.8
SBI,SBN5-5	0.75	344	579	369	604	141	115	—	23.4	24.3
SBI,SBN5-6	1.1	371	606	396	631	141	115	—	25.1	26.0
SBI,SBN5-7	1.1	398	633	423	658	141	115	—	25.6	26.5
SBI,SBN5-8	1.1	425	660	450	685	141	115	—	26.1	27.1
SBI,SBN5-9	1.5	468	759	493	784	177	141	—	35.4	36.4
SBI,SBN5-10	1.5	495	786	520	811	177	141	—	36.0	36.9
SBI,SBN5-11	2.2	522	813	547	838	177	141	—	39.3	40.3
SBI,SBN5-12	2.2	549	840	574	865	177	141	—	39.9	40.8
SBI,SBN5-13	2.2	576	867	601	892	177	141	—	40.4	41.4
SBI,SBN5-14	2.2	603	894	628	919	177	141	—	41.0	41.9
SBI,SBN5-15	2.2	630	921	655	946	177	141	—	41.5	42.5
SBI,SBN5-16	2.2	657	948	682	973	177	141	—	42.1	43.0
SBI,SBN5-18	3	715	1031	740	1056	197	147	—	50.3	51.3
SBI,SBN5-20	3	769	1085	794	1110	197	147	—	51.6	52.5
SBI,SBN5-22	4	823	1149	848	1174	220	161	—	55.8	56.8
SBI,SBN5-24	4	877	1203	902	1228	220	161	—	56.9	57.8
SBI,SBN5-26	4	931	1257	956	1282	220	161	—	58.0	58.9
SBI,SBN5-29	4	1012	1338	1037	1363	220	161	—	59.7	60.6
SBI,SBN5-32	5.5	1123	1485	1148	1510	235	197	300	84.9	85.8
SBI,SBN5-36	5.5	1231	1593	1256	1618	235	197	300	87.1	88.1


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 10




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SB 10



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
	[kW]	H1	H2				
SB 10-1	0.37	343	538	141	115	—	35.9
SB 10-2	0.75	347	582	141	115	—	38.2
SB 10-3	1.1	377	612	141	115	—	40.3
SB 10-4	1.5	423	714	177	141	—	50.1
SB 10-5	2.2	453	744	177	141	—	53.9
SB 10-6	2.2	483	774	177	141	—	55.0
SB 10-7	3	518	834	197	147	—	63.8
SB 10-8	3	548	864	197	147	—	64.9
SB 10-9	3	578	894	197	147	—	65.9
SB 10-10	4	608	934	220	161	—	70.3
SB 10-12	4	668	994	220	161	—	72.4
SB 10-14	5.5	760	1122	235	197	300	104.1
SB 10-16	5.5	820	1182	235	197	300	106.2
SB 10-18	7.5	880	1278	235	197	300	113.6
SB 10-20	7.5	940	1338	235	197	300	116.7
SB 10-22	7.5	1000	1398	235	197	300	118.8


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SBI, SBN 10



Pump type	Motor P ₂ [kW]	SBI, SBN								
		Dimension [mm]							Net weight [kg]	
		Victaulic		DIN flange		D1	D2	D3	Victaulic	DIN flange
		H1	H2	H1	H2					
SBI,SBN10-1	0.37	353	548	353	548	141	115	—	31.6	31.4
SBI,SBN10-2	0.75	357	592	357	592	141	115	—	34.3	34.2
SBI,SBN10-3	1.1	387	622	387	622	141	115	—	36.4	36.3
SBI,SBN10-4	1.5	433	724	433	724	177	141	—	46.1	46.0
SBI,SBN10-5	2.2	463	754	463	754	177	141	—	50.0	49.8
SBI,SBN10-6	2.2	493	784	493	784	177	141	—	51.0	50.8
SBI,SBN10-7	3	528	844	528	844	197	147	—	59.1	58.9
SBI,SBN10-8	3	558	874	558	874	197	147	—	60.1	60.0
SBI,SBN10-9	3	588	904	588	904	197	147	—	61.1	61.0
SBI,SBN10-10	4	618	944	618	944	220	161	—	65.6	65.4
SBI,SBN10-12	4	678	1004	678	1004	220	161	—	67.6	67.5
SBI,SBN10-14	5.5	770	1132	770	1132	235	197	300	100.4	100.3
SBI,SBN10-16	5.5	830	1192	830	1192	235	197	300	102.5	102.4
SBI,SBN10-18	7.5	890	1288	890	1288	235	197	300	110.9	110.8
SBI,SBN10-20	7.5	950	1348	950	1348	235	197	300	113.0	112.8
SBI,SBN10-22	7.5	1010	1408	1010	1408	235	197	300	115.1	114.9


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 15




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SB 15



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
	[kW]	H1	H2				
SB 15-1	1.1	400	635	141	115	—	43.8
SB 15-2	2.2	415	706	177	141	—	55.7
SB 15-3	3	465	781	197	147	—	64.9
SB 15-4	4	510	836	220	161	—	69.7
SB 15-5	4	555	881	220	161	—	71.2
SB 15-6	5.5	632	994	235	197	300	102.3
SB 15-7	5.5	677	1039	235	197	300	103.8
SB 15-8	7.5	722	1120	235	197	300	111.8
SB 15-9	7.5	767	1165	235	197	300	113.3
SB 15-10	11	889	1394	318	154	300	150.0
SB 15-12	11	979	1484	318	154	300	153.0
SB 15-14	11	1069	1574	318	154	300	156.3
SB 15-17	15	1204	1714	318	154	300	171.5


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SBI, SBN 15



Pump type	Motor P ₂ [kW]	SBI, SBN								
		Dimension [mm]							Net weight [kg]	
		Victaulic		DIN flange		D1	D2	D3	Victaulic	DIN flange
		H1	H2	H1	H2					
SBI,SBN15-1	1.1	387	622	397	632	141	115	—	36.0	36.6
SBI,SBN15-2	2.2	403	694	413	704	177	141	—	47.7	48.3
SBI,SBN15-3	3	453	769	463	779	197	147	—	56.1	56.7
SBI,SBN15-4	4	498	824	508	834	220	161	—	61.0	61.6
SBI,SBN15-5	4	543	869	553	879	220	161	—	62.4	63.0
SBI,SBN15-6	5.5	620	982	630	992	235	197	300	94.6	95.3
SBI,SBN15-7	5.5	665	1027	675	1037	235	197	300	96.1	96.7
SBI,SBN15-8	7.5	710	1108	720	1118	235	197	300	104.1	104.7
SBI,SBN15-9	7.5	755	1153	765	1163	235	197	300	105.6	106.2
SBI,SBN15-10	11	877	1382	887	1392	318	154	350	142.7	143.3
SBI,SBN15-12	11	967	1472	977	1482	318	154	350	145.5	146.2
SBI,SBN15-14	11	1057	1562	1067	1572	318	154	350	148.5	149.1
SBI,SBN15-17	15	1192	1702	1202	1712	318	154	350	162.9	163.5


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 20




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SB 20



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
		H1	H2				
SB 20-1	1.1	400	636	141	115	—	43.9
SB 20-2	2.2	415	708	177	141	—	55.7
SB 20-3	4	465	795	220	161	—	68.3
SB 20-4	5.5	542	910	235	197	300	99.4
SB 20-5	5.5	587	955	235	197	300	100.8
SB 20-6	7.5	632	1038	235	197	300	108.6
SB 20-7	7.5	677	1083	235	197	300	110.1
SB 20-8	11	799	1315	318	245	350	147.1
SB 20-10	11	889	1405	318	245	350	150.0
SB 20-12	15	979	1504	318	245	350	163.1
SB 20-14	15	1069	1594	318	245	350	166.0
SB 20-17	18.5	1204	1773	318	245	350	195.4


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights – SBI, SBN 20



Pump type	Motor	SBI , SBN								
		Dimension [mm]							Net weight [kg]	
		Victaulic		DIN flange		D1	D2	D3	Victaulic	DIN flange
		P ₂ [kW]	H1	H2	H1					
SBI,SBN20-1	1.1		387	623	397	141	115	—	36.0	36.6
SBI,SBN20-2	2.2		403	696	413	177	141	—	47.7	48.3
SBI,SBN20-3	4		453	783	463	220	161	—	59.5	60.2
SBI,SBN20-4	5.5		530	898	540	235	197	300	91.7	92.3
SBI,SBN20-5	5.5		575	943	585	235	197	300	93.2	93.8
SBI,SBN20-6	7.5		620	1026	630	235	197	300	100.9	101.6
SBI,SBN20-7	7.5		665	1071	675	235	197	300	102.4	103.0
SBI,SBN20-8	11		787	1303	797	318	245	350	139.7	140.3
SBI,SBN20-10	11		877	1393	887	318	245	350	142.7	143.3
SBI,SBN20-12	15		967	1492	977	318	245	350	155.7	156.3
SBI,SBN20-14	15		1057	1582	1067	318	245	350	158.6	159.2
SBI,SBN20-17	18.5		1192	1761	1202	318	245	350	187.8	188.5


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 32




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights-SB32



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	DIN flange		D1	D2	D3	DIN flange	
	[kW]	H1					H2
SB 32-1-1	1.5	504	795	177	141	280	71.5
SB 32-1	2.2	504	795	177	141	280	74.3
SB 32-2-2	3	574	935	197	147	280	84.2
SB 32-2	4	574	900	220	161	280	87.6
SB 32-3-2	5.5	644	1006	235	197	300	110.2
SB 32-3	5.5	644	1006	235	197	300	110.2
SB 32-4-2	7.5	714	1112	235	197	300	119.5
SB 32-4	7.5	714	1112	235	197	300	119.5
SB 32-5-2	11	894	1399	318	245	350	163.3
SB 32-5	11	894	1399	318	245	350	163.3
SB 32-6-2	11	964	1469	318	245	350	166.3
SB 32-6	11	964	1469	318	245	350	166.3
SB 32-7-2	15	1034	1544	318	245	350	179.5
SB 32-7	15	1034	1544	318	245	350	179.5
SB 32-8-2	15	1104	1614	318	245	350	182.6
SB 32-8	15	1104	1614	318	245	350	182.6
SB 32-9-2	18.5	1174	1724	318	245	350	210.6
SB 32-9	18.5	1174	1724	318	245	350	210.6
SB 32-10-2	18.5	1244	1794	318	245	350	212.7
SB 32-10	18.5	1244	1794	318	245	350	213.7
SB 32-11-2	22	1314	1894	358	265	350	258.8
SB 32-11	22	1314	1894	358	265	350	258.8
SB 32-12-2	22	1384	1964	358	265	350	260.8
SB 32-12	22	1384	1964	358	265	350	260.8
SB 32-13-2	30	1454	2114	420	295	400	328.2
SB 32-13	30	1454	2114	420	295	400	328.2
SB 32-14-2	30	1524	2184	420	295	400	331.3
SB 32-14	30	1524	2184	420	295	400	331.3


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights-SBI,SBN32



Pump type	Motor	SBI,SBN					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
	[kW]	H1	H2				DIN flange
SBI,SBN 32-1-1	1.5	504	795	177	141	280	66.5
SBI,SBN 32-1	2.2	504	795	177	141	280	69.3
SBI,SBN 32-2-2	3	574	935	197	147	280	79.1
SBI,SBN 32-2	4	574	900	220	161	280	82.5
SBI,SBN 32-3-2	5.5	644	1006	235	197	300	105.1
SBI,SBN 32-3	5.5	644	1006	235	197	300	105.1
SBI,SBN 32-4-2	7.5	714	1112	235	197	300	114.5
SBI,SBN 32-4	7.5	714	1112	235	197	300	114.6
SBI,SBN 32-5-2	11	894	1399	318	245	350	158.2
SBI,SBN 32-5	11	894	1399	318	245	350	158.3
SBI,SBN 32-6-2	11	964	1469	318	245	350	161.3
SBI,SBN 32-6	11	964	1469	318	245	350	161.4
SBI,SBN 32-7-2	15	1034	1544	318	245	350	174.6
SBI,SBN 32-7	15	1034	1544	318	245	350	174.6
SBI,SBN 32-8-2	15	1104	1614	318	245	350	177.9
SBI,SBN 32-8	15	1104	1614	318	245	350	177.9
SBI,SBN 32-9-2	18.5	1174	1724	318	245	350	205.5
SBI,SBN 32-9	18.5	1174	1724	318	245	350	205.6
SBI,SBN 32-10-2	18.5	1244	1794	318	245	350	208.1
SBI,SBN 32-10	18.5	1244	1794	318	245	350	208.2
SBI,SBN 32-11-2	22	1314	1894	358	265	350	253.6
SBI,SBN 32-11	22	1314	1894	358	265	350	253.6
SBI,SBN 32-12-2	22	1384	1964	358	265	350	256.3
SBI,SBN 32-12	22	1384	1964	358	265	350	256.3
SBI,SBN 32-13-2	30	1454	2114	420	295	400	323.6
SBI,SBN 32-13	30	1454	2114	420	295	400	323.6
SBI,SBN 32-14-2	30	1524	2184	420	295	400	326.3
SBI,SBN 32-14	30	1524	2184	420	295	400	326.3


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 45




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights-SB45



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	DIN flange		D1	D2	D3	DIN flange	
	P ₂	H1					H2
[kW]							
SB 45-1-1	3	561	877	197	147	280	91.7
SB 45-1	4	561	887	220	161	280	95.1
SB 45-2-2	5.5	641	1003	235	197	300	118.3
SB 45-2	7.5	641	1039	235	197	300	124.6
SB 45-3-2	11	831	1336	318	245	350	169.0
SB 45-3	11	831	1336	318	245	350	169.0
SB 45-4-2	15	911	1421	318	245	350	182.9
SB 45-4	15	911	1421	318	245	350	182.9
SB 45-5-2	18.5	991	1541	318	245	350	211.6
SB 45-5	18.5	991	1541	318	245	350	211.6
SB 45-6-2	22	1071	1651	358	265	350	258.1
SB 45-6	22	1071	1651	358	265	350	258.1
SB 45-7-2	30	1151	1811	420	295	400	326.4
SB 45-7	30	1151	1811	420	295	400	326.5
SB 45-8-2	30	1231	1891	420	295	400	330.2
SB 45-8	30	1231	1891	420	295	400	331.3
SB 45-9-2	30	1311	1971	420	295	400	334.0
SB 45-9	37	1311	1971	420	295	400	347.0
SB 45-10-2	37	1391	2051	420	295	400	350.7
SB 45-10	37	1391	2051	420	295	400	350.7
SB 45-11-2	45	1471	2161	470	325	450	412.5
SB 45-11	45	1471	2161	470	325	450	412.5
SB 45-12-2	45	1551	2241	470	325	450	416.2
SB 45-12	45	1551	2241	470	325	450	416.2
SB 45-13-2	45	1631	2321	470	325	450	419.9


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights-SBI,SBN45



Pump type	Motor	SBI,SBN					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	DIN flange
	[kW]	H1	H2				
SBI,SBN45-1-1	3	559	875	197	147	280	82.9
SBI,SBN 45-1	4	559	885	220	161	280	86.3
SBI,SBN 45-2-2	5.5	639	1001	235	197	300	109.5
SBI,SBN 45-2	7.5	639	1037	235	197	300	115.8
SBI,SBN 45-3-2	11	829	1334	318	245	350	160.2
SBI,SBN 45-3	11	829	1334	318	245	350	160.2
SBI,SBN 45-4-2	15	909	1419	318	245	350	174.1
SBI,SBN 45-4	15	909	1419	318	245	350	174.1
SBI,SBN 45-5-2	18.5	989	1539	318	245	350	202.8
SBI,SBN 45-5	18.5	989	1539	318	245	350	202.8
SBI,SBN 45-6-2	22	1069	1649	358	265	350	249.3
SBI,SBN 45-6	22	1069	1649	358	265	350	249.3
SBI,SBN 45-7-2	30	1149	1809	420	295	400	317.7
SBI,SBN 45-7	30	1149	1809	420	295	400	317.7
SBI,SBN 45-8-2	30	1229	1889	420	295	400	321.4
SBI,SBN 45-8	30	1229	1889	420	295	400	321.5
SBI,SBN 45-9-2	30	1309	1969	420	295	400	325.2
SBI,SBN 45-9	37	1309	1969	420	295	400	338.2
SBI,SBN 45-10-2	37	1389	2049	420	295	400	341.9
SBI,SBN 45-10	37	1389	2049	420	295	400	341.9
SBI,SBN 45-11-2	45	1469	2159	470	325	450	403.7
SBI,SBN 45-11	45	1469	2159	470	325	450	403.7
SBI,SBN 45-12-2	45	1549	2239	470	325	450	407.4
SBI,SBN 45-12	45	1549	2239	470	325	450	407.4
SBI,SBN 45-13-2	45	1629	2319	470	325	450	411.1


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 64




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS


Dimensions and weights-SB-64



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
	[kW]	H1	H2				
SB 64-1-1	4	563	889	220	161	280	88.9
SB 64-1	5.5	563	613	235	197	300	108.3
SB 64-2-2	7.5	646	702	235	197	300	118.7
SB 64-2-1	11	756	1261	318	245	350	159.3
SB 64-2	11	756	1261	318	245	350	159.3
SB 64-3-2	15	838	1348	318	245	350	174.0
SB 64-3-1	15	838	1348	318	245	350	174.0
SB 64-3	18.5	838	1388	318	245	350	198.9
SB 64-4-2	18.5	921	1471	318	245	350	202.9
SB 64-4-1	22	921	1501	358	265	350	245.7
SB 64-4	22	921	1501	358	265	350	245.7
SB 64-5-2	30	1003	1663	420	295	400	314.3
SB 64-5-1	30	1003	1663	420	295	400	314.3
SB 64-5	30	1003	1663	420	295	400	314.3
SB 64-6-2	30	1086	1746	420	295	400	318.2
SB 64-6-1	37	1086	1746	420	295	400	331.2
SB 64-6	37	1086	1746	420	295	400	331.2
SB 64-7-2	37	1168	1828	420	295	400	335.3
SB 64-7-1	37	1168	1828	420	295	400	335.3
SB 64-7	45	1172	1862	470	325	450	393.4
SB 64-8-2	45	1255	1945	470	325	450	397.5
SB 64-8-1	45	1255	1945	470	325	450	397.5



Dimensions and weights-SB(I/N)-64



Pump type	Motor	SBI,SBN					
		Dimension[mm]					Net weight [kg]
	P ₂ [kW]	DIN flange		D1	D2	D3	
		H1	H2				DIN flange
SBI,SBN 64-1-1	4	563	889	220	161	280	81.8
SBI,SBN 64-1	5.5	563	613	235	197	300	101.3
SBI,SBN 64-2-2	7.5	646	702	235	197	300	111.7
SBI,SBN 64-2-1	11	756	1261	318	245	350	152.3
SBI,SBN 64-2	11	756	1261	318	245	350	152.3
SBI,SBN 64-3-2	15	838	1348	318	245	350	166.5
SBI,SBN 64-3-1	15	838	1348	318	245	350	166.5
SBI,SBN 64-3	18.5	838	1388	318	245	350	191.4
SBI,SBN 64-4-2	18.5	921	1471	318	245	350	195.4
SBI,SBN 64-4-1	22	921	1501	358	265	350	238.1
SBI,SBN 64-4	22	921	1501	358	265	350	238.1
SBI,SBN 64-5-2	30	1003	1663	420	295	400	306.7
SBI,SBN 64-5-1	30	1003	1663	420	295	400	306.7
SBI,SBN 64-5	30	1003	1663	420	295	400	306.7
SBI,SBN 64-6-2	30	1086	1746	420	295	400	310.7
SBI,SBN 64-6-1	37	1086	1746	420	295	400	323.7
SBI,SBN 64-6	37	1086	1746	420	295	400	323.7
SBI,SBN 64-7-2	37	1168	1828	420	295	400	327.7
SBI,SBN 64-7-1	37	1168	1828	420	295	400	327.7
SBI,SBN 64-7	45	1172	1862	470	325	450	385.8
SBI,SBN 64-8-2	45	1255	1945	470	325	450	390.0
SBI,SBN 64-8-1	45	1255	1945	470	325	450	390.0


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

SB, SBI, SBN 90




Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights-SB90



Pump type	Motor	SB					
		Dimension[mm]					Net weight [kg]
	P ₂	DIN flange		D1	D2	D3	
	[kW]	H1	H2				
SB 90-1-1	5.5	572	934	235	197	300	122.2
SB 90-1	7.5	572	970	235	197	300	128.5
SB 90-2-2	11	774	1279	318	245	350	174.4
SB 90-2	15	774	1284	318	245	350	184.5
SB 90-3-2	18.5	866	1416	318	245	350	214.7
SB 90-3	22	866	1446	358	265	350	257.5
SB 90-4-2	30	958	1618	420	295	400	327.3
SB 90-4	30	958	1618	420	295	400	327.3
SB 90-5-2	37	1050	1710	420	295	400	346.9
SB 90-5	37	1050	1710	420	295	400	346.9
SB 90-6-2	45	1142	1832	470	325	450	410.2
SB 90-6	45	1142	1832	470	325	450	410.3


Technical data

Vertical Multistage Centrifugal In-line Pumps



STAIRS PUMPS

Dimensions and weights-SBI,SBN90



Pump type	Motor	SBI,SBN					
		Dimension[mm]					Net weight [kg]
	P ₂ [kW]	DIN flange		D1	D2	D3	
		H1	H2				
SBI,SBN 90-1-1	5.5	576	938	235	197	300	112.1
SBI,SBN 90-1	7.5	576	974	235	197	300	118.4
SBI,SBN 90-2-2	11	778	1283	318	245	350	164.2
SBI,SBN 90-2	15	778	1288	318	245	350	174.3
SBI,SBN 90-3-2	18.5	870	1420	318	245	350	204.4
SBI,SBN 90-3	22	870	1450	358	265	350	247.2
SBI,SBN 90-4-2	30	962	1622	420	295	400	316.9
SBI,SBN 90-4	30	962	1622	420	295	400	316.9
SBI,SBN 90-5-2	37	1054	1714	420	295	400	336.9
SBI,SBN 90-5	37	1054	1714	420	295	400	337.0
SBI,SBN 90-6-2	45	1146	1836	470	325	450	400.0
SBI,SBN 90-6	45	1146	1836	470	325	450	400.1