

EVO

LED RANGE



START FLOOD

Slimline, durable and high performance LED floodlights



The new **Start Flood** range of exterior LED floodlights incorporates the latest high powered COB LED technology into a slimline die-cast aluminium body. The standard floodlight version is IP65 weatherproof (PIR IP44) and is available in both 3000K and 4000K. All products include 1m stripped cable making the product quick to install while the PIR version comes with a 8m range and 120 detection angle

Ideal for residential or small business premises, these slimline floodlights have been designed to be more aesthetically pleasing than the

standard large and bulky floodlight. The PIR version has the PIR incorporated into the floodlight reducing the footprint of the product. The PIR also has adjustable lux and time levels allowing the PIR to trigger the floodlight in certain light levels and for a predetermined amount of time.

The range is available in 10W, 26W and 50W which are direct replacements for the light output of the standard floodlight halogen R7s (48W, 120W and 230W) but with at least 80% of the energy savings.

START FLOOD

Slimline, durable and high performance LED floodlights

FEATURES

- Slimline exterior LED floodlight with/without PIR
- Ideal for residential or small office/warehouse applications
- Durable die-cast aluminium body with tilting bracket
- IP65 weatherproof (IP44 Sensor)
- Adjustable lux (0 to 1000lux) and time levels (10 secs to 12min)
- Direct replacement for energy inefficient Halogen R7s (10W = 48W / 26W = 120W / 50W = 230W)
- High lumen efficacy of up to 94lm/W
- Lifetime : 30.000hrs
- Quick and easy to install as includes 1m pre-wired stripped cable and fittings



Includes 1m pre-wired cable




Slimline floodlight



*PIR Version Only


Item Code	Description	EAN	Body Colour	IP rating	Colour temperature (K)	Voltage (V)	Power consumption (W)	Luminous Flux (lm)	Lifetime (h)
0047830	START FLOOD LED 800LM 10W 3000K	5410288478302	Black	IP65	3000	220-240	10	800	30,000
0047831	START FLOOD LED 850LM 10W 4000K	5410288478319	Black	IP65	4000	220-240	10	850	30,000
0047832	START FLOOD LED 800LM 10W PIR 3000K	5410288478326	Black	IP44	3000	220-240	10	800	30,000
0047833	START FLOOD LED 850LM 10W PIR 4000K	5410288478333	Black	IP44	4000	220-240	10	850	30,000
0047822	START FLOOD LED 2100LM 26W 3000K	5410288478227	Black	IP65	3000	220-240	26	2100	30,000
0047823	START FLOOD LED 2300LM 26W 4000K	5410288478234	Black	IP65	4000	220-240	26	2300	30,000
0047824	START FLOOD LED 2100LM 26W PIR 3000K	5410288478241	Black	IP44	3000	220-240	26	2100	30,000
0047825	START FLOOD LED 2300LM 26W PIR 4000K	5410288478258	Black	IP44	4000	220-240	26	2300	30,000
0047826	START FLOOD LED 4400LM 50W 3000K	5410288478265	Black	IP65	3000	220-240	50	4400	30,000
0047827	START FLOOD LED 4700LM 50W 4000K	5410288478272	Black	IP65	4000	220-240	50	4700	30,000
0047828	START FLOOD LED 4400LM 50W PIR 3000K	5410288478289	Black	IP44	3000	220-240	50	4400	30,000
0047829	START FLOOD LED 4700LM 50W PIR 4000K	5410288478296	Black	IP44	4000	220-240	50	4700	30,000

Dimension (mm)



Floodlight IP65

	A	B	C	D
10W	149	113	122	49.3
26W	194.5	151.3	180	59.5
50W	268.3	220.7	220.7	70.8




Floodlight with Sensor (IP44)


	A	B	C	D
10W	171	131.3	150	61.1
26W	213	181.1	181.1	69
50W	268.3	220.6	220.6	82

Photometric Data


3,000K - 10W




4,000K - 10W




3,000K - 26W



4,000K - 26W



3,000K - 50W



4,000K - 50W

